

		metric   imperial	TANK.G 2600		
<b>Axes Configuration</b>			<b>4-Axes</b>	<b>5-Axes</b>	<b>5 Axes-Multitasking</b>
<b>Process Technology</b>			–	Milling	Milling, Turning, Grinding
<b>Working Area</b>	<i>X-Axis Stroke</i>	mm   in.	2.600   102.4	2.600   102.4	2.600   102.4
	<i>Y-Axis Stroke</i>	mm   in.	2.000   78.7	1.700   66.9	1.700   66.9
	<i>Z-Axis Stroke</i>	mm   in.	2.000   78.7	2.000   78.7	2.000   78.7
	<i>X/Y/Z Axis Rapid Feed</i>	m/min   ipm	40   1,574.8	40   1,574.8	45   1,771.7
<b>Pallet</b>	<i>Option 1</i>	mm   in.	1.000 x 1.000   39.3 x 39.3	1.000 x 1.000   39.3 x 39.3	Ø 1.000   Ø 39.3
	<i>Option 2<sup>2</sup></i>	mm   in.	1.250 x 1.250   49.2 x 49.2	1.250 x 1.250   49.2 x 49.2	Ø 1.250   Ø 49.2
<b>Rotary Table (B-Axis)</b>	<i>Max. Rotation Speed</i>	min-1	20	20	200
<b>5th Axis (A-Axis)</b>	<i>Type</i>		–	Tilting Head	Tilting Head
	<i>Tilting Angle</i>	Degrees	–	175 (+80/-95)	175 (+80/-95)
<b>Spindle Unit</b>	<i>Tool-Taper</i>		HSK / ISO / CAPTO		
	<i>Speed Range</i>	min-1	from 6.000 to 30.000		
<b>Tool-Magazine</b>	<i>Capacity (up to)1</i>	No.	80 (999)	80 (999)	80 (999)
<b>Available Configurations</b>			Single-Pallet/ Twin-Pallet / Multipallet / FMS		