

| | | metric imperial | TANK 1000 | |
|---------------------------------|------------------------------|-------------------|---|----------------------------|
| Axes Configuration | | | 5-Axes | 5-Axes Multitasking |
| Process Technology | | | Milling | Milling, Turning, Grinding |
| Working Area | <i>X-Axis Stroke</i> | mm in. | 1.200 47.2 | 1.200 47.2 |
| | <i>Y-Axis Stroke</i> | mm in. | 1.000 39.4 | 1.000 39.4 |
| | <i>Z-Axis Stroke</i> | mm in. | 1.100 43.3 | 1.100 43.3 |
| | <i>X/Y/Z Axis Rapid Feed</i> | m/min ipm | 75 2,952.8 | 75 2,952.8 |
| Pallet | <i>Option 1</i> | mm in. | 630 x 630 24.8 x 24.8 | Ø 800 Ø 31.5 |
| | <i>Option 2²</i> | mm in. | 630 x 800 24.8 x 31.5 | – |
| Rotary Table (B-Axis) | <i>Max. Rotation Speed</i> | min-1 | 100 | 100 / 800 |
| 5th Axis (A-Axis) | <i>Type</i> | | Tilting Head | Tilting Head |
| | <i>Tilting Angle</i> | Degrees | 180 (+80/-100) | 180 (+80/-100) |
| Spindle Unit | <i>Tool-Taper</i> | | HSK / ISO / CAPTO | |
| | <i>Speed Range</i> | min-1 | from 14.000 up to 18.000 | |
| Tool-Magazine | <i>Capacity (up to)1</i> | No. | 89 (999+) | 89 (999+) |
| Available Configurations | | | Single-Pallet / Twin-Pallet / Multipallet / FMS | |