

		metric   imperial	TANK 1300		
<b>Axes Configuration</b>			<b>4-Axes</b>	<b>5-Axes</b>	<b>5 Axes-Multitasking</b>
<b>Process Technology</b>			Milling	Milling	Milling, Yurning, Grinding
<b>Working Area</b>	<i>X-Axis Stroke</i>	mm   in.	1.300   51.2	1.300   51.2	1.300   51.2
	<i>Y-Axis Stroke</i>	mm   in.	1.300   51.2	1.400   55.1	1.400   55.1
	<i>Z-Axis Stroke</i>	mm   in.	1.300   51.2	1.400   55.1	1.560   61.4
	<i>X/Y/Z Axis Rapid Feed</i>	m/min   ipm	50   1,968.5	50   1,968.5	50   1,968.5
<b>Pallet</b>	<i>Option 1</i>	mm   in.	630 x 800   24.8 x 31.5	630 x 800   24.8 x 31.5	Ø 860   Ø 33.9
	<i>Option 2<sup>2</sup></i>	mm   in.	800 x 800   31.5 x 31.5	800 x 800   31.5 x 31.5	Ø 1.000   Ø 39.3
<b>Rotary Table (B-Axis)</b>	<i>Max. Rotation Speed</i>	min-1	20 / 40	20 / 40	500
<b>5th Axis (A-Axis)</b>	<i>Type</i>		-	Tilting Head	Tilting Head
	<i>Tilting Angle</i>	Degrees	-	175 (+80/-95)	175 (+80/-95)
<b>Spindle Unit</b>	<i>Tool-Taper</i>		HSK / ISO / CAPTO		
	<i>Speed Range</i>	min-1	from 6.000 up to 30.000		
<b>Tool-Magazine</b>	<i>Capacity (up to)</i>	No.	80 (999)	80 (999)	80 (999)
<b>Available Configurations</b>			Single-Pallet/ Twin-Pallet / Multi-Pallet / FMS		